



Advanced Lubricants Technology

Page 1 of 2

RACING+ FULLY SYNTHETIC 100% PAO+ESTER SAE 5W50 API SN UHR

Product Data Sheet

PERENNIAL RACING+ FULLY SYNTHETIC 100% PAO+ESTER UHR SAE 5W50 SN- LOW FRICTION & TURBO POWER

High Performance Premium Racing Fully Synthetic 100% PAO+ESTER Gasoline Engine Oil with “**UHR™ Technology**”

PRODUCT FEATURES

PERENNIAL RACING+ FULLY SYNTHETIC 100% PAO+ESTER UHR SAE 5W50 SN is an advanced fully synthetic PAO+ESTER formulation, SHEAR FREE with the latest “**UHR™ Technology**” additive system. UHR™ Technology improved the overall performance of engine oil and provides excellent low friction, engine cleanliness, oxidation control, strong acid neutralisation capability and long drain capability. It is designed to provide superior engine responsiveness and extends the engine life with its outstanding protection against engine wear and corrosion.

PERENNIAL RACING + FULLY SYNTHETIC 100% PAO + ESTER UHR SAE 5W50 SN provides easy start-up at temperatures as low as -36 °C.

At high operating temperatures, **PERENNIAL RACING + FULLY SYNTHETIC 100% PAO + ESTER UHR SAE 5W50 SN** maintains its lubricity and thermal stability to provide a highly efficient lubricating film to engine parts that prevents sludge formation and oxidation thickening, it is specially formulated for today's sophisticated, high revving, hot running engines.

PERENNIAL RACING + FULLY SYNTHETIC 100% PAO + ESTER UHR SAE 5W50 SN enhances engine performance to attain longer engine life, easy starting, improved power and fuel economy.

APPLICATIONS

PERENNIAL RACING + FULLY SYNTHETIC 100% PAO + ESTER UHR SAE 5W50 SN is designed for use in modern 4,6 & 8+ cylinder, multi cam, multi valve including VVT, naturally aspired, supercharged & turbocharged engines. It can be used in high performance, modern engines for both competition and normal on road use in a wide range of vehicles.

PERENNIAL RACING + FULLY SYNTHETIC 100% PAO + ESTER UHR SAE 5W50 SN is suitable for vehicles that specify the use of **SAE 5W-30** viscosity engine oils in owners handbook. It is also suitable for use in LPG and light duty diesel engines where API CF, ACEA A1/B1 or A5/B5 is recommended. It is NOT suitable for use in diesels fitted with a DPF (Diesel Particulate Filter) and 4 stroke motorcycles with wet clutches.

It's SHEAR FREE formulation eliminates viscosity loss during extreme engine operating conditions ensuring the ultimate in protection for your engine.

PERENNIAL RACING + FULLY SYNTHETIC 100% PAO + ESTER UHR SAE 5W50 SN has been proven in race and competition conditions in engine requiring a high performance fully synthetic engine oil. It is the product of choice for many competitors running competition vehicles in circuit & drag racing, rallying, drifting, hill clim, targa, time trials and regularity.

NOTE : When changing oil, **PERENNIAL** recommend using **PERENNIAL FLUSH EZ** series, fast acting, solvent/solvent free, engine cleaning formulation that removes engine deposits, sludge and contaminations with oil reserve drain. It contains added zinc for engine wear protection and its fast acting formulation works in 10 minutes.

For product safety and handling information, refer to Material Safety Data Sheet.



Advanced Lubricants Technology

Page 2 of 2

RACING+ FULLY SYNTHETIC 100% PAO+ESTER SAE 5W50 API SN UHR

SPECIAL PROPERTIES

- ◆ OEM level of quality.
- ◆ Long service life for the engines due to a very high level protection against wear
- ◆ Rapid oil delivery at low temperatures
- ◆ Optimal oil pressure at all engine speeds
- ◆ Tested with catalytic converters and performance proven with turbochargers
- ◆ Stable performance in a wide range of temperatures due to PAO+ESTER base oil.
- ◆ Help to reduce fuel consumption, reduce wear when start-up.
- ◆ Extra cleaning performance to help prevent the formation of sludge and harmful deposits.
- ◆ Keeps your engine running like new.
- ◆ Outstanding thermal and oxidation stability to reduce oil aging allowing extended drain interval protection.
- ◆ Excellent overall lubrication and wear protection performance for all driving styles and conditions High oxidation stability and strong resistance to high and low temperature sludge formation.

PERFORMANCE LEVELS

The performance and environmental characteristics of product exceed most of the requirements of Japanese, European and American automotive manufacturers and meet standards of API, ACEA, Mercedes-Benz, BMW, GM, Renault, Volvo, Toyota, Lexus, Honda, Nissan, Mazda, Daihatsu and etc

- ◆ API SN/CF, ILSAC GF5, ACEA C3-10, BMW Longlife-04, GM Dexos 2, MB p229.51, MB p229.31*, MB p226.5* and Porsche A40*, Renault RN0700*, Renault RN0710*, Ford WSS, Volkswagen 502.00/505.00.
- ◆ ACEA A3/B3-08, ACEA A3/B4-08
- ◆ JASO MA
- ◆ * Viscosity SAE 5W-30 Only.
- ◆ ILSAC GF-4/GF-5

TYPICAL SPECIFICATION

		SAE 5W-50	
PROPERTY	UNIT	METHOD	SPECIFICATION
Appearance	-	Visual	Bright & Clear
Colour	-	ASTM D1500	3
Density@15 °C	kg/l	ASTM D4052	0.865
Viscosity at 40 °C	cSt	ASTM D445	113.5
Viscosity at 100 °C	cSt	ASTM D445	18.5
Viscosity Index	-	ASTM D 2270	184
Flash Point COC	°C	ASTM D 92	Min 215
Total Base Number	mgKOH/g	ASTM D2896	9.75
Pour Point	°C	ASTM D 97	-45
Cold Crank Vis@-30 °C	cP	ASTM D5293	5100

** The above specifications are typical of current production, variation in these characteristics may occur, but will not affect the product performance.*